



ICE 12.1 P

Description

12" passive subwoofer designed for behind the screen or acoustic wall installation. Recommended for small to mid-size rooms. Can be used as an additional subwoofer together with the ICE 15.2P in multiple subwoofer installation.

Specifications

Nominal impedance	8 Ohms
Power handling capacity	
Continuous	350 W (AES)
Peak	700 W (AES)
Sensitivity	92dB (1m/1W)
SPL	115dB continuous, 121dB peak (1/8 space, 1m), maximum output: 121dB @ 50 Hz
Frequency response	36Hz (- 3dB)
Drivers	300 mm long-throw driver with 76 mm voice coil
Cabinet	68L sealed box made of premium quality Baltic birch plywood internally cross braced. Black structured painting
Dimensions (HxWxD)	800 (810 with damping feet) x 550 x 230 mm
Weight	24 kg

Features

- 1/ 2 steel secure rings with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals in parallel with Neutrik Speakon connectors
- 4/ Back and front terminals. "Cabinet through" cable tunnel for front terminal access
- 5/ Rear cable channel for close to wall placement
- 6/ Just 230 mm in depth cabinet

