



## ICE 12.2 P

### Description

12" subwoofer with 12" front firing passive radiator. Shallow cabinet for behind the screen or acoustic wall installation. Recommended for small to mid-size rooms.

### Specifications

Nominal impedance	8 Ohms
Power handling capacity	Continuous 350 W (AES) Peak 700 W (AES)
Sensitivity SPL	92dB (1m/1W) 115dB continuous, 121dB peak (1/8 space, 1m) Maximum output 121 dB @ 50 Hz
Frequency response	28Hz (-3dB)
Drivers	300 mm long-throw driver with 75 mm voice coil and 300 mm passive radiator
Cabinet	86L bass reflex enclosure with front firing radiator Cabinet is made of premium quality Baltic birch plywood internally cross braced. Black structured painting
Dimensions (HxWxD)	1100 (1110 with damping feet ) x 550 x 230 mm
Weight	30,5 kg

### Features

- 1/ 2 steel secure rings with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals in parallel with Neutrik Speakon connectors
- 4/ Back and front terminals. "Cabinet through" cable tunnel for front terminal access
- 5/ Rear cable channel for close to wall placement
- 6/ Just 230 mm in depth cabinet

