



ICE S 15.1 HS

Description

ICE 15.1 HS is 3 way high end quality loudspeaker designed for large home theaters. It capable to create reference SPL in rooms from 10 to 20 m deep.

Specifications

| | | |
|-------------------------|----------------|---|
| Nominal impedance | | 8 Ohms |
| Power handling capacity | | |
| | Continuous | 500 W (IEC 268-5) |
| | Peak | 1000 W (IEC 268-5) |
| Sensitivity | | 97dB (1m/1W) |
| SPL | | 120dB continuous, 127dB peak (1/8 space, 1m) |
| Frequency response | | 45Hz (-10dB) 70Hz – 20kHz (-3dB) |
| Crossover | | 2th Order, 350 Hz, 1.8 kHz. Audiophile parts and point to point soldering |
| Drivers | Bass | 380 mm with 77 mm coils in 55 litre sealed box |
| | Midrange | 200 mm driver with 51,7 mm voice coil |
| | High Frequency | Pleated diaphragm tweeter with horn directivity (-6dB) 80°H x 30°V from 1.5 kHz |
| Cabinet | | Cabinet made of high quality MDF, internally braced. Light absorbing black soft touch coating |
| Dimensions (HxWxD) | | 764 x 460 x 255 mm |
| Weight | | 40,5 kg |

Features

- 1/ Steel secure ring with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals
- 4/ Rear cable channel for close to wall placement
- 5/ Light absorbing soft touch coating
- 6/ Shallow cabinet - only 255 mm deep

