



ICE 8.2 HS

Description

ICE 8.2 HS is very powerful loudspeaker designed for large home theaters. It can be used as main speaker in rooms from 10 to 16 m deep. As surround loudspeaker alongside with the ICE 15.1 HS it becomes part of the reference quality sounding home cinema system.

Specifications

Nominal impedance		4 Ohms
Power handling capacity		
	Continuous	500 W (IEC 268-5)
	Peak	1000 W (IEC 268-5)
Sensitivity		96dB (1m/1W)
SPL		118dB continuous, 124dB peak (1/8 space, 1m)
Frequency response		43Hz (-10dB) 58Hz – 20kHz (-3dB)
Crossover		2th Order, 1.8 kHz. Audiophile parts and point to point soldering
Drivers	Midrange	2x200 mm custom driver with 62,4 mm voice coil
	High Frequency	Pleated diaphragm tweeter with horn, directivity (-6dB) 80°H x 30°V from 1.5 kHz. Rotatable HF module allows for vertical or horizontal loudspeaker orientation
Cabinet		38L vented cabinet made of high quality MDF, internally braced. Light absorbing black soft touch coating
Dimensions (HxWxD)		764 x 460 x 202 mm
Weight		28,5 kg

Features

- 1/ Steel secure ring with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals
- 4/ Rear cable channel for close to wall placement
- 5/ Light absorbing soft touch coating
- 6/ Shallow cabinet - only 202 mm deep

