



ICE S 6.1

Description

ICE S 6.1 is designed for behind the screen or behind the acoustic wall installation. But also can be used as the book shelf or wall mounted speaker in the living room. ICE S 6.1 is perfect as an immersive audio format upper channel.

Specifications

Nominal impedance	8 Ohms	
Power handling capacity	Continuous	60 W (IEC 268 – 5)
	Peak	120 W (IEC 268 – 5)
Sensitivity	89dB (1m/1W)	
Maximum SPL	110dB continuous, 116dB peak (1/8 space, 1m)	
Frequency response	60Hz(-10dB) 70Hz - 20kHz (-3dB)	
Crossover	2th Order, 2.1kHz , 80Hz subwoofer crossover point. Audiophile grade components and point to point wiring	
Drivers		
Midrange	High output 165 mm driver with 32 mm voice coil.	
High Frequency	30 mm fabric tweeter with waveguide	
Cabinet	18L sealed box made of high quality MDF internally braced. Light absorbing black soft touch coating	
Dimensions (HxWxD)	400 x 400 x 145 mm	
Weight	9 kg	

Features

- 1/ Steel secure ring with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals
- 4/ Rear cable channel for close to wall placement
- 5/ M6 holes for 200 mm square brackets
- 6/ Light absorbing soft touch coating

